



## Kompositebänder CS

Beschreibung	Breite	Länge	Zugfestigkeit	Hülse-Diameter	Rollen/ Kart.	Rollen/ Palette
CS 40	13 mm	1100 m	300 kp	200 mm	2 pcs	60 pcs
CS 50	16 mm	850 m	425 kp	200 mm	2 pcs	60 pcs
CS 60	19 mm	600 m	475 kp	200 mm	2 pcs	60 pcs
CS 55	16 mm	600 m	550 kp	200 mm	2 pcs	60 pcs
CS 65	19 mm	450 m	625 kp	200 mm	2 pcs	60 pcs
CS 85	25 mm	450 m	785 kp	200 mm	2 pcs	60 pcs
CS 86	25 mm	400 m	1025 kp	200 mm	2 pcs	60 pcs
CSL 105	32 mm	300 m	1200 kp	200 mm	2 pcs	60 pcs
CS 105	32 mm	300 m	1600 kp	200 mm	2 pcs	60 pcs

Hyvelvägen 1, S-668 32 Ed, Sweden  
Phone. +46 (0)534 - 668 00, Fax. +46 (0)534 - 668 01  
Email: [lianpac.ed@swipnet.se](mailto:lianpac.ed@swipnet.se) • [www.lianpac.com](http://www.lianpac.com)